NARVIK 557

Pobrano z mamadecor.pl

Narvik 557XX0016
23.07.2021 v.16.6
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Four side light distribution covered from the top.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information

Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Mounting of the luminaire: 6 oval holes 10x15 with a diameter of ø172mm every 60 ° Other accessories must be purchased separately
Terminal	Connection terminals: max 3x4mm², Possibility to connect the luminaire in loops max 3x2.5mm². Round insulated cable with a maximum diameter of ø12.5mm. The luminaire is equipped with an inspection door
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	10,84kg / 13,16kg
Box dimensions [cm]	31,5x29x99

Technical data

LED module	Philips Fortimo SLM C 1208 L15 2024 G7 (Datasheet)
Driver	Philips Xitanium 36W/m 929001486006 (Datasheet)
Light source wattage	19W
Luminaire wattage	21,8W
Lamp luminous flux	3137lm
Luminaire luminous flux	556lm
Light source efficiency	165,1lm/W
Efficiency of the luminaire	25,5lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
THD factor	20%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	4,6A / 65µs

Maximum number of luminaires of this type per MCB:

B 10A: 21, **B 16A**: 34, **C 10A**: 35, **C 16A**: 57

Accessories sold separately

110GA0009	Ground anchor
505ZX0009	Concreting anchor

Spare parts

ZS557zx0016	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
557AL	ALUMINIUM	9006
557GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not affect the quality of the luminaire