VISBY 577

Pobrano z mamadecor.pl

Visby 577XX0309
23.07.2021 v.09.4
www.norlys.com

Type of luminaire

Type of lumianire	Pole luminaire.
Photometric body	Indirect light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Pole top luminaire for installation on a lighting pole with Ø60mm mounting cap.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket.
Mounting method	Fixing of the luminaire: fitting to Ø60mm pole.
Terminal	4.5m cable (H05VV-F 3G1 type), for connection inside the lighting pole (in appropriately selected electrical installation box).
Type of light source	LED module AC integrated
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	7,28kg / 8,92kg
Side area of luminaire	0,086m^2

Technical data

LED module	Philips Fortimo LED DLM ES 3000lm G2
Light source wattage	27W
Luminaire wattage	27W
Lamp luminous flux	2950lm
Luminaire luminous flux	1388lm
Light source efficiency	109,3lm/W
Efficiency of the luminaire	51,4lm/W
ULOR	3%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF>0,90
Ta Rated temperature	+25°C
This product contains light source of energy efficiency class	
Inrush current	2,63A/47,27µs

Accessories sold separately , xx - color of the luminaire

3005XX0009	Telescopic lighting pole with adjustable height 3600 ... 4500mm, mounting cap Ø76.
7660XX0009	Reduction for Ø60 luminaires for mounting on the Ø76 pole .
7662ZX0009	EK480 pole connector with 6A fuse.
7664ZX0009	100kg concrete foundation for pole installation.

Spare parts

0905770101	Electric set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
577AL	ALUMINIUM	9006
577GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.