

KIRUNA 598

Pobrano z mamadecor.pl

Kiruna 598XX0009
23.07.2021 v.09.1
www.norlys.com





Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Luminaire with stable and durable construction. For use in private and public areas requiring high resistance to external mechanical damage.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter ø7...10,5mm.
Type of light source	E27 lamp

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Recommended light sources

Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Retrofit/Advanced/ Classic B38 E14	Philips Master LED luster/candle/frosted B38 E14

Files to download

Manual

Indexes

Index	Color	RAL
598AL	ALUMINIUM	9006
598GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no



Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.