EGERSUND PARK 6105

Pobrano z mamadecor.pl

Egersund park
6105XX0309
24.04.2020 v.09.13
www.norlys.com

Type of luminaire

Photometric body	Symmetric light directed down.
Characteristics of the luminaire	Pole luminaire, mounted ø120mm.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket. Nylon6 cable gland.
Mounting method	Luminaire mounting: 3 ø9mm holes with ø65mm diameter every 120 °
Terminal	Hermetic box IP68: Connection terminals: max 4x4mm², Possibility of connecting the luminaire in a max 4x2,5mm² loop. Cable in a round tire with a diameter of ø8 ... 12mm or ø10 ... 14mm The luminaire is equipped with an revision door.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	13kg / 14,01kg
Box dimensions [cm]	15x15x260
Side area of luminaire	0,33m^2

Technical data

Luminaire wattage	10W
Luminaire luminous flux	959lm
Light source efficiency	110lm/W
Efficiency of the luminaire	95,9lm/W
ULOR	2%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Energy Efficiency Index	
Power Factor luminaire	PF >0,97
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-30...+25°C
Inrush current	150mA / 500µs

Accessories sold separately

6130zx0009	Concreting anchor

Spare parts

46999402	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
6105AL	ALUMINIUM	9006
6105GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing it. Due to the dynamic development of lighting technology, additional information is available upon request. LED modules must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.