Pobrano z mamadecor.pl

BERLIN 617

Berlin 617XX0012
23.07.2021 v.12.2
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Light partly covered from the top.
Characteristics of the luminaire	Plafond type luminaire with modern design.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø4,2mm, spacing 155x40mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,7kg / 2,05kg
Box dimensions [cm]	27,5x27,5x15

Technical data

LED module	LUMENS LED DLM90C/230V/A 830
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Luminaire luminous flux	276lm
Light source efficiency	110lm/W
Efficiency of the luminaire	27,6lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,90
Ta Rated temperature	+25°C
This product contains light source of energy efficiency class	
Inrush current	150mA / 500µs

Spare parts

06620003	Lens.
46999402	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
617B	BLACK	9005
617W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.