BASEL 660

Pobrano z mamadecor.pl

Basel 660XX0009
23.07.2021 v.09.1
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire.

General information

Materials	Base - powder painted aluminum cast. Front - stainless steel , hot dip galvanized steel, powder coated steel. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 138x50mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	2,94kg / 3,64kg
Box dimensions [cm]	27,5x22,8x33,5

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 57W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

46999021	LED E27 lamp.

Recommended light sources

Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06660004	Lens.
08652662	Gasket.

Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

Indexes

Index	Color	RAL
660B	BLACK	9005
660GA	GALVANIZED	-
660ST	STAINLESS STEEL	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.