BASEL 681

Pobrano z mamadecor.pl

Basel 681XX0009
23.07.2021 v.09.2
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire.

General information

Materials	Base - powder painted aluminum cast. Front - stainless steel , hot dip galvanized steel, powder coated steel. Lens - safety glass, satin. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 138x50mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,8kg / 3,7kg
Box dimensions [cm]	27,5x22,8x33,5

Technical data

LED module	Lumens LNM/140X30/4R5W/830/230V/C
Light source wattage	4,5W
Luminaire wattage	4,5W
Lamp luminous flux	428lm
Luminaire luminous flux	231lm
Light source efficiency	95,1lm/W
Efficiency of the luminaire	51,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,99
Ta Rated temperature	+25°C
Max ambient temperature	+35°C

This product contains light source of energy efficiency class

Inrush current	27,2mA/500µs

Maximum number of luminaires of this type per MCB:

B 10A: 95, **B 16A**: 151, **C 10A**: 157, **C 16A**: 256

Spare parts

06660005	Lens.
08652662	Gasket.
46999394	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
681B	BLACK	9005
681GA	GALVANIZED	-
681ST	STAINLESS STEEL	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.