

LARVIK 690

Pobrano z mamadecor.pl

Larvik 690XX0009
23.07.2021 v.09.2
www.norlys.com





Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	Wall-mounted luminaire in Scandinavian design, for general use. Possibility to install on corners of architectural objects. IP of lighting chamber - 55.

General information

Materials	Hot-dip galvanized steel. Powder painted steel. Lens - clear polycarbonate, UV stabilized. EPDM cable gland.
Mounting method	Fixing the luminaire: using the attached mounting box.
Terminal	Connection terminals: max 2x2,5mm². Possibility to connect luminaire in loop max 2x1,5mm². A round wire in the isolation with a diameter of ø6...10mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	2,2kg / 3kg
Box dimensions [cm]	32,3x32,3x36

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 57W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

153XX0009	Mounting corner
159XX0009	Luminaire mounting distance
46999021	LED E27 lamp

Recommended light sources

Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06240003	Lens.

Files to download

Manual

Indexes

Index	Color	RAL
690B	BLACK	9005
690GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no



Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.