NORDLAND 719

Pobrano z mamadecor.pl

Type of luminaire

Type of lumianire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	A ceiling luminaire with a modern design. For lighting private areas and other architectural concepts

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø5mm, spacing 150x170mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². Round insulated cable with a diameter ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,43kg / 2,77kg
Box dimensions [cm]	30,5x30,5x11

Technical data

Light source wattage	12,9W
Luminaire wattage	12,9W
Lamp luminous flux	1500lm
Luminaire luminous flux	739lm
Light source efficiency	116,3lm/W
Efficiency of the luminaire	57,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Spare parts

06720002	Lens.
ZS719zx0011	Service set.

Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual
BIM Revit	BIM ArchiCAD

Indexes

Index	Color	RAL
719AL	ALUMINIUM	9006
719GR	GRAPHITE	7016
719W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not affect the quality of the luminaire