KOSTER 725

Pobrano z mamadecor.pl

Koster 725XX0012
23.07.2021 v.12.6
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Modern design wall-mounted luminaire. Possibility to install on corners of architectural objects.

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. EPDM cable gland.
Mounting method	Fixing of the luminaire: 3 holes ø7mm, spacing according to the attached mounting box.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	2,86kg / 3,74kg
Box dimensions [cm]	43,5x29x24

Technical data

LED module	Philips Fortimo DLM ES 1100/8xx G2 (Datasheet)
Light source wattage	9,5W
Luminaire wattage	9,5W
Lamp luminous flux	1080lm
Luminaire luminous flux	872lm
Light source efficiency	113,7lm/W
Efficiency of the luminaire	91,8lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,9
THD factor	< 30%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Inrush current	2,98A / 34,07µs

Maximum number of luminaires of this type per MCB:

B 10A: 144, **B 16A**: 230, **C 10A**: 239, **C 16A**: 391

Accessories sold separately , xx - color of the luminaire

158XX0009	Mounting corner.

Spare parts

06710000	Lens.
46999749	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
725AL	ALUMINIUM	9006
725GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.