NICE 777

Pobrano z mamadecor.pl

Nice 777XX0015
23.07.2021 v.15.7
www.norlys.com

Type of luminaire

Type of lumianire	Pole luminaire.
Photometric body	Indirect symmetrical light.
Characteristics of the luminaire	A mounted luminaire designed to be mounted on a lighting pole with a Ø60mm mounting shaft

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Luminaire mounting: luminaire adapted to a ø60mm pole, 95mm deep. Other accessories must be purchased separately
Terminal	H05VV-F 3G1 cable, 4.5 m long, to be connected inside the pole (in a properly selected electric box)
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	9,18kg / 11,75kg
Box dimensions [cm]	80x62x62
Side area of luminaire	0,1m^2

Technical data

LED module	Philips SLM C 830 1211 L19 2828 G7
Driver	Philips Xitanium 36W/m 929001486006 (Datasheet)
Light source wattage	33,9W
Luminaire wattage	36,4W
Lamp luminous flux	5127lm
Luminaire luminous flux	3190lm
Light source efficiency	151,2lm/W
Efficiency of the luminaire	87,6lm/W
ULOR	6,84%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
Power Factor luminaire	PF 0,97
Ta Rated temperature	+25°C
Max ambient temperature	+35°C
This product contains light source of energy efficiency class	
Inrush current	4,6A / 65µs

Accessories sold separately

7662ZX0009	EK480 pole connector with IP54, fuse D01 / E14 max16A
7664ZX0009	100 kg concrete foundation for mounting lighting pole

Spare parts

ZS777zx0015	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
777AL	ALUMINIUM	9006
777GR	GRAPHITE	7016

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not affect the quality of the luminaire