SANDVIK 795

Pobrano z mamadecor.pl

Sandvik 795XX0010
23.07.2021 v.10.2
www.norlys.com

Type of luminaire

Type of lumianire	Ceiling luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 68x68mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED Gu10 lamp
Net weight of luminaire	0,59kg
Box dimensions [cm]	12x8,5x13,5

Technical data

LED GU10 lamp	LED PAR16
Light source wattage	max 4W
Lamp luminous flux	~ 250lm
Light source efficiency	62,5lm/W

This product contains light source of energy efficiency class

Possibility to order luminaire with LED GU10 lamp Philips Master LEDspot MV 250lm / 4W / 2700K / 25D (dimmable).

Accessories sold separately

06790005	Lens.
46102501	LED GU10 lamp.

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10	Philips Master LED max 4W PAR16 Gu10

Files to download

3D models and drawings	Manual

Indexes

Index	Color	RAL
795AL	ALUMINIUM	9006
795B	BLACK	9005
795GR	GRAPHITE	7016
795W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.