FIRENZE 805

Pobrano z mamadecor.pl

Firenze 805XX0011
23.07.2021 v.11.5
www.norlys.com

Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Classic design luminaire. For lighting gardens, private areas and public spaces. Other accessories need to be purchased separately.

General information

Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. EPDM cable gland.
Mounting method	Fixing the luminaire: 2 holes ø5mm, spacing 90mm.
Terminal	Connection terminals: max 2x2,5mm², possibility to connect luminaire in loop max 2x1,5mm². A round wire in the isolation with a diameter of max ø7...10,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	2,65kg / 3,55kg
Box dimensions [cm]	24,5x23x82

Technical data

Light source wattage	MAX 57W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class

Accessories sold separately

307ZX0009	Concreting anchor.
46999021	LED E27 lamp.

Recommended light sources

Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06370797	Lens.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
805B	BLACK	9005
805W	WHITE	9003

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.