# FIRENZE 810

Pobrano z mamadecor.pl

Firenze 810XX0309
23.07.2021 v.09.1
www.norlys.com

## Type of luminaire

| | |
|---|---|
| Type of lumianire | Accessories |
| Photometric body | Uncovered light. |
| Characteristics of the luminaire | Classic design luminaire, mounted on a telescopic lighting pole.<br>Adjustable height 1930..2560mm.<br>For lighting gardens, terraces and other architectural concepts. |

## General information

| | |
|---|---|
| Materials | Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized.<br>Silicone gasket. |
| Mounting method | Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø240mm every 120°.<br>Set contains:<br>Art. 8012 - luminaire,<br>Art. 3040 - reduction,<br>Art. 3010 - lightning pole.<br>Other accessories need to be purchased separately. |
| Terminal | Connection terminal: max. 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation with a diameter of max ø6...12,5mm. |
| Type of light source | E27 lamp |
| Net / gross weight of luminaire | 9,23kg / 11,92kg |

## Technical data

| | |
|---|---|
| E27 lamp | QA55 / LED A55..60 |
| Light source wattage | MAX 57W / LED 9W |
| Ta Rated temperature | +25°C |

This product contains light source of energy efficiency class

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

## Accessories sold separately

| | |
|---|---|
| 108GA0009 | Anchoring support. |
| 305ZX0009 | Concreting anchor. |
| 306ZX0009 | Ground anchor. |
| 46999021 | LED E27 lamp. |

## Recommended light sources

| | |
|---|---|
| Osram ECO PRO Classic 57<=>75W E27 | Philips ECO Classic 53<=>75W E27 |
| Osram LED Parathom Classic / Retrofit E27 | Philips Master LEDbulb / Classic / CorePro E27 |

## Spare parts

| | |
|---|---|
| 06370797 | Lens. |

## Files to download

| | |
|---|---|
| Photometric LDT files | Photometric IES files |
| Manual | |

## Indexes

| Index | Color | RAL |
|---|---|---|
| **810B** | BLACK | 9005 |
| **810W** | WHITE | 9003 |

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.