BODEN 866

Pobrano z mamadecor.pl

Boden 866XX0012
23.07.2021 v.12.6
www.norlys.com

Type of luminaire

Type of lumianire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	A ceiling-type luminaire with modern design

General information

Materials	Base - powder painted aluminum cast. Front - hot-dip galvanized steel or aluminum cast powder painted. Lens - milky polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Mounting of the luminaire: 2 holes ø4,5mm, spacing 90x160mm
Terminal	Connection terminals: max 3x2,5mm², Possibility to connect luminaire in loop max 3x1,5mm², Round insulated cable with a diameter of ø7...10,5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,57kg / 1,74kg
Box dimensions [cm]	34x16,5x11,5

Technical data

LED module	Lumens EDC 57C 8W xxx 230V A FF Ver.1.0 (Datasheet)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	890lm
Luminaire luminous flux	451lm
Light source efficiency	111,3lm/W
Efficiency of the luminaire	56,4lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class

Inrush current	2,9A/34µs

Spare parts

06860003	Lens.
08550009	Gasket.
46999552	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
866B	BLACK	9005
866GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

Before the installation, please read the instructions attached to the luminaire. Due to the dynamic development of lighting technology, we provide additional information at the client's request. LED module replaceable by a person with appropriate qualifications, following applicable regulations. Condensation, which may occur in luminaires, is a natural phenomenon and does not deteriorate the quality of the luminaire