

Pobrano z mamadecor.pl



FRASER LED

PMMA, stal chromowana / PMMA, electroplated steel /
PMMA, ôÔĘÁ8ÔĘƷŢáŢ℘ ÕÔð ð ð


6945 ◯ CH



FRASER LED

PMMA, stal chromowana / PMMA, electroplated steel /
PMMA, ôÔĘÁ8ÔĘƷŢáŢ℘ ÕÔð ð ð

6944 ◯ CH




FRASER LED

PMMA, stal chromowana / PMMA, electroplated steel /
PMMA, ôÔĘÁ8ÔĘƷŢáŢ℘ ÕÔð ð ð

6943 ◯ CH

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION
6943	1×6W LED	4000K	360 lm	120°	80	~220-240V, 50Hz	⧈	0,8	IP 44
6944	1×8W LED	4000K	420 lm	120°	80	~220-240V, 50Hz	⧈	0,8	IP 44
6945	1×12W LED	4000K	720 lm	120°	80	~220-240V, 50Hz	⧈	0,8	IP 44




BRAZOS

stal chromowana, szkło / electroplated steel, glass /
ôÔĘÁ8ÔĘƷŢáŢ℘ ÕÔŢzŁ, ÕÔð ð ð ð

6948 ◯ CH

1×G9, max 25W

IP 44




BRAZOS

stal chromowana, szkło / electroplated steel, glass /
ôÔĘÁ8ÔĘƷŢáŢ℘ ÕÔŢzŁ, ÕÔð ð ð ð

6950 ◯ CH

2×G9, max 25W

IP 44



BRAZOS

stal chromowana, szkło / electroplated steel, glass /
ôÔĘÁ8ÔĘƷŢáŢ℘ ÕÔŢzŁ, ÕÔð ð ð ð

6951 ◯ CH

3×G9, max 25W

IP 44