Pobrano z mamadecor.pl

[redacted]

LUMINAIRE PHOTOMETRIC TEST REPORT

8757 CTLS NEA LED WHITE 20W, 3000K, ANGLE36Á

Description Lines

Manufacturer:	NOWODVORSKI LIGHTING
Model name:	8757 CTLS NEA LED WHITE 20W,3000K,ANGLE36
File name:	8757 CTLS NEA LED WHITE 20W,3000K,ANGLE36.ldt
Date:	2019-08-19
Report number:	EF 19/08/2019/43; EF 07/11/2019/44
Length:	150 mm
Width:	63 mm
Height:	195 mm
IP rating:	IP 20
Protection class:	I
Dimmable:	No

Equipment

Test system:	EVERFINE GO-2000B_V1 SYSTEM V2.00.417
Temperature:	25 +/-1 ÁC
Humidity:	65.0%
ɔ interval:	2 deg
C interval:	10 deg
ɔ range:	0-180 deg
Measurement distance:	6.56 m


Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czňstochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

Photometric data

Total luminous flux:	1713.69 lm
Color temperature:	3063 K
x:	0.4327
y:	0.4028
Color rendering index:	92.3
Wattage:	19.222 W
U	230.52 V
I	0.0856 A
Power factor:	0,9737
Luminous efficacy:	88.49 lm/W
Flux in lower hemisphere:	98.6%
Flux in upper hemisphere:	1.4%
Maximum luminous intensity:	4100 cd
Light output ratio (LOR):	100.00%



Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

[redacted]

Spectral distribution

[redacted]

Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

LUMINAIRE PHOTOMETRIC TEST REPORT

8757 CTLS NEA LED WHITE 20W, 3000K, ANGLE15Á

Description Lines

Manufacturer:	NOWODVORSKI LIGHTING
Model name:	8756 CTLS NEA LED WHITE 20W,4000K,ANGLE15
File name:	8756 CTLS NEA LED WHITE 20W,4000K,ANGLE15.ldt
Date:	2019-08-19
Report number:	EF 19/08/2019/40; EF 07/11/2019/44
Length:	150 mm
Width:	63 mm
Height:	195 mm
IP rating:	IP 20
Protection class:	I
Dimmable:	No

Equipment

Test system:	EVERFINE GO-2000B_V1 SYSTEM V2.00.417
Temperature:	25 +/-1 ÁC
Humidity:	65.0%
ɔ interval:	2 deg
C interval:	10 deg
ɔ range:	0-180 deg
Measurement distance:	6.56 m


Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czňstochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

Photometric data

Total luminous flux:	1701.9 lm
Color temperature:	3063 K
x:	0.4327
y:	0.4028
Color rendering index:	92.3
Wattage:	19.25 W
U	229.71 V
I	0.0859 A
Power factor:	0,9742
Luminous efficacy:	88.12 lm/W
Flux in lower hemisphere:	98.6%
Flux in upper hemisphere:	1.4%
Maximum luminous intensity:	11770 cd
Light output ratio (LOR):	100.00%



Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

[redacted]

Spectral distribution

[redacted]

Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl



LUMINAIRE PHOTOMETRIC TEST REPORT

8757 CTLS NEA LED WHITE 20W, 3000K, ANGLE23Á

Description Lines

Manufacturer:	NOWODVORSKI LIGHTING
Model name:	8757 CTLS NEA LED WHITE 20W,3000K,ANGLE23
File name:	8757 CTLS NEA LED WHITE 20W,3000K,ANGLE23.ldt
Date:	2019-08-19
Report number:	EF 19/08/2019/42; EF 07/11/2019/44
Length:	150 mm
Width:	63 mm
Height:	195 mm
IP rating:	IP 20
Protection class:	I
Dimmable:	No

Equipment

Test system:	EVERFINE GO-2000B_V1 SYSTEM V2.00.417
Temperature:	25 +/-1 ÁC
Humidity:	65.0%
ɔ interval:	2 deg
C interval:	10 deg
ɔ range:	0-180 deg
Measurement distance:	6.56 m


Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

Photometric data

Total luminous flux:	1668.84 lm
Color temperature:	3063 K
x:	92.3
y:	0.4327
Color rendering index:	0.4028
Wattage:	19.222 W
U	230.52 V
I	0.0856 A
Power factor:	0,9737
Luminous efficacy:	86.82 lm/W
Flux in lower hemisphere:	98.6%
Flux in upper hemisphere:	1.4%
Maximum luminous intensity:	8130 cd
Light output ratio (LOR):	100.00%



Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com

Pobrano z mamadecor.pl

[redacted]

[redacted]

Spectral distribution

[redacted]

Nowodworski sp. j.
ul. Bojemskiego 11, 42-202 Czństochowa, POLSKA, NIP: PL 5731015208
Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com