
Pobrano z mamadecor.pl

STRAIGHT CEILING LED L 7551

STRAIGHT CEILING LED M 7558

STRAIGHT CEILING LED S 7597




STRAIGHT CEILING LЛцCD L

painted steel, plastic PMMЛ

7ЛцCЛцC; 7ЛцCЛцC; 7ЛцCЛцCЛцC

1xLED TUBE T8, max 22W, included




STRAIGHT CEILING LЛцCD M

painted steel, plastic PMMЛ

7ЛцCЛцC; 7ЛцCЛцC; 7ЛцCЛцCЛцC

1xLED TUBE T8, max 16W, included



STRAIGHT CEILING LЛцCD ЛцC

painted steel, plastic PMMЛ

7ЛцCЛцC; 7ЛцCЛцC7

1xLED TUBE T8, max 11W, included

Name	ЛцCize	Power	Colour temp.	Luminous flux	ЛцCeam angle	Colour ЛцCendering Index ЛцCCЛцCIЛцC	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120 °	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120 °	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120 °	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS

GRAPHITE P010 RAL 7016 WHITE P004 RAL 9003 BLACK P013 RAL 9005