Pobrano z mamadecor.pl

10125B/W/W

25W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The IP54 Bathroom Downlights
Order Code	10125B/W/W
Colour	White
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular

Pobrano z mamadecor.pl

Height	46mm
Diameter	228mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	32V
Safety Class	
Power(Watts)	22,5W
IP Rating	IP54
Light Source	LED built in

Pobrano z mamadecor.pl

LED Type	SMD 2835
LED Brand	Epistar
LED Number	60
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	16,8-26,6W
Power Factor	0,9
Constant Current	Yes
Output	720mA
Voltage Range	24-38V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	70°C
Housing Material	Plastic
Output Terminal	Cable
Brand	0
Protection	Short Circuit and Overload

Illumination Data

Colour Temperature	3000K
Lumen Output	1875lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	90°

Pobrano z mamadecor.pl

Illumination Diagram	

Packing Info

Box Length	26cm
Box Width	26cm
Box Height	7,5cm
Box Weight	1,2Kg
Pcs/Carton	10
Barcode	5291889043225
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes