Pobrano z mamadecor.pl

07 Downlights Adjustable LED>The COB Extractable Range

11110F/W/C

10W COB LED extractable fitting with great flexibility on movement. Ideal for shops.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Physical Specification

Item Group	07 Downlights Adjustable LED
Family	The COB Extractable Range
Order Code	11110F/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	76mm

Pobrano z mamadecor.pl

Diameter	108mm
Cutout Hole Diameter	90mm
Recessed Ceiling	Yes
Depth Required	105mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	200mA
Voltage	37,3V
Safety Class	
Power(Watts)	7,5W
IP Rating	IP20
Light Source	LED built in
LED Type	COB

Pobrano z mamadecor.pl

LED Brand	Citizen

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	5,4-8,4W
Power Factor	0,9
Constant Current	Yes
200mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Eaglerise

Illumination Data

Colour Temperature	4000K
Lumen Output	800lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	

Packing Info

Box Length	11,5cm
Box Width	11,5cm
Box Height	11cm
Box Weight	0,43kg

Pobrano z mamadecor.pl

Pcs/Carton	36
Barcode	5291889044840
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes