Pobrano z mamadecor.pl

07 Downlights Adjustable LED>The COB Recessed Range Die cast

11125RA/W/C

25W COB LED recessed adjustable spot, for general lighting applications.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Physical Specification

Item Group	07 Downlights Adjustable LED
Family	The COB Recessed Range Die cast
Order Code	11125RA/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	125mm

Pobrano z mamadecor.pl

Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	40V
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Pobrano z mamadecor.pl

F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-30W
Power Factor	0,9
Constant Current	Yes
700mA	25.5-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Brand	Eaglerise
Protection	Short circuit Protection

Illumination Data

Colour Temperature	4000K
Lumen Output	1900lm
Light Efficiency	76lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Pobrano z mamadecor.pl

Box Length	20,5cm
Box Width	15cm
Box Height	15cm
Box Weight	1Kg
Pcs/Carton	12
Barcode	5291889047766
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes