Pobrano z mamadecor.pl

13 Wall & Ceiling LED>The SMD Cylinders Aluminium

12125L/W/W

25W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12125L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	115mm
Diameter	162mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Pobrano z mamadecor.pl

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	600mA
Voltage	40V
Power(Watts)	24W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5630
LED Brand	Samsung
LED Number	48

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	16,2-25,2W

Pobrano z mamadecor.pl

Power Factor	0,9
Constant Current	Yes
600mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

Illumination Data

Colour Temperature	3000K
Lumen Output	2050lm
Light Efficiency	82lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Length	17,5cm
Box Width	17,5cm
Box Height	12,5cm
Box Weight	0.827kg
Pcs/Carton	36
Barcode	5291889041009
HS Code	9405409900

Pobrano z mamadecor.pl

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes