Pobrano z mamadecor.pl

10120/W

20W LED recessed downlight with interchangeable rings, IP44.
Ideal for general lighting applications.

Rings must be order separately.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Must be ordered separately

10100/AL

10100/G

10100/W

Pobrano z mamadecor.pl

Physical Specification

Item Group	06 Downlights Fixed LED
Family	Round Downlights
Order Code	10120/W
Material	Aluminium
Shape	Circular
Height	50mm
Diameter	202mm
Cutout Hole Diameter	180mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	500mA

Pobrano z mamadecor.pl

Voltage	38V
Safety Class	
Power(Watts)	19W
IP Rating	IP44
Light Source	LED built in
LED Brand	Epistar
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,5-21W
Power Factor	0,9
Constant Current	Yes
500mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	1800lm
Light Efficiency	90lm/W
CRI	75

Pobrano z mamadecor.pl

Beam Angle	110°
Illumination Diagram	

Packing Info

Box Length	23,5cm
Box Width	7,5cm
Box Height	21,5cm
Box Weight	1,03Kg
Pcs/Carton	10
Barcode	5291889032120
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes