Pobrano z mamadecor.pl

06 Downlights Fixed LED>Square UGR17 & UGR19 Office Panels Aluminium

50140U/W/C

60x60 UGR 17 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with 1000mA driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Accessories

050017

Related items

89050L

89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED

Pobrano z mamadecor.pl

Family	Square UGR17 & UGR19 Office Panels Aluminium
Order Code	50140U/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	595mm
Width	595mm
Height	10mm
Recessed T-Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	1000mA
Voltage	36V

Pobrano z mamadecor.pl

Safety Class	
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 4014
LED Brand	Sanan

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	25-42W
Power Factor	0,9
Constant Current	Yes
1000mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-30? ~ +50?
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	No-Load, Short Circuit

Illumination Data

Colour Temperature	4000K
Lumen Output	3400lm
Light Efficiency	85lm/W
CRI	80
Beam Angle	120°

Pobrano z mamadecor.pl

Illumination Diagram	
UGR	17

Packing Info

Box Weight	2,4Kg
Pcs/Carton	6
Barcode	5291889054894
HS Code	9405109890

Energy Label

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes