Pobrano z mamadecor.pl

06 Downlights Fixed LED>The 8-16W Square Recessed Panels Die cast

50108F/G/D

8W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms.

Supplied with 500mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 8-16W Square Recessed Panels Die cast
Order Code	50108F/G/D
Colour	Grey
Material	Die Cast
Diffuser Material	Acrylic
Shape	Rectangular

Pobrano z mamadecor.pl

Length	108mm
Width	108mm
Height	20mm
Cutout Hole Width	96mm
Cutout Hole Length	96mm
Recessed Ceiling	Yes
Depth Required	40mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	500mA
Voltage	14V
Safety Class	
Power(Watts)	7W
IP Rating	IP40

Pobrano z mamadecor.pl

Light Source	LED built in
LED Type	SMD 2016
LED Brand	Epistar
LED Number	52

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	5,5-7W
Power Factor	0,9
Constant Current	Yes
500mA	11-14V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	85°C
Housing Material	Plastic
Brand	ONE LIGHT Ltd

Illumination Data

Colour Temperature	6000K
Lumen Output	461lm
Light Efficiency	57,62lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Pobrano z mamadecor.pl

Box Length	17cm
Box Width	15cm
Box Height	3cm
Box Weight	0,335Kg
Pcs/Carton	40
Barcode	5291889039747
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes