Pobrano z mamadecor.pl

50140B/W/D

60x60 recessed backlit LED panel for T-rail false ceilings. Uniform lighting, ideal for commercial applications.

Complete with 850mA driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Related items

050017

050108

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 40W Backlit Panel

Pobrano z mamadecor.pl

Order Code	50140B/W/D
Colour	White
Material	Aluminium + Steel
Shape	Rectangular
Length	595mm
Width	595mm
Height	29mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	850mA
Voltage	45V
Safety Class	

Pobrano z mamadecor.pl

Power(Watts)	38,7W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Samsung

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,3-38,25W
Power Factor	0,9
Constant Current	Yes
850mA	38-45V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Cable Length	50cm
Brand	ONE

Illumination Data

Colour Temperature	6000K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Pobrano z mamadecor.pl

Packing Info

Box Weight	2.300kg
Pcs/Carton	4
Barcode	5291889071105
HS Code	9405119090

Certification & Warranty

Warranty	3 years
Weee Directive	Yes