Pobrano z mamadecor.pl

50143F/W/D

60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with 1200mA driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Accessories

050017 050108

Related items

89048T 89050L 89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED

Pobrano z mamadecor.pl

Family	The 48W Square Panels Aluminium
Order Code	50143F/W/D
Colour	White
Material	Aluminium
Shape	Rectangular
Length	595mm
Width	595mm
Height	10mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	1200mA
Voltage	38V

Pobrano z mamadecor.pl

Safety Class	
Power(Watts)	45,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,4-50,4W
Power Factor	0,9
Constant Current	Yes
1200mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Weled
Protection	No-Load, Short Circuit

Illumination Data

Colour Temperature	6000K
Lumen Output	3800lm
Light Efficiency	79,16lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Pobrano z mamadecor.pl

Packing Info

Box Weight	4,3Kg
Pcs/Carton	4
Barcode	5291889036203
HS Code	9405109890

Energy Label

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes