Pobrano z mamadecor.pl

50148AU/W/W

UGR19 62x62 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Must be ordered separately

89048

Accessories

050017

050108

Related items

Pobrano z mamadecor.pl

89048T

89050L

89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	Panels For Germany/Austria
Order Code	50148AU/W/W
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	620mm
Width	620mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	1200mA
Safety Class	
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in

Pobrano z mamadecor.pl

LED Type	SMD 2835
LED Brand	Epistar
LED Number	240

Illumination Data

Colour Temperature	3000K
Lumen Output	4000lm
Light Efficiency	83,33lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	
UGR	19

Packing Info

Box Length	72cm
Box Width	65cm
Box Height	4,5cm
Box Weight	3,4Kg
Pcs/Carton	4
Barcode	5291889044628
HS Code	9405109890

Certification & Warranty

Pobrano z mamadecor.pl

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes