Pobrano z mamadecor.pl



# 50148E/W/W

60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.

## Downloads

## Dimensions

## Must be ordered separately

89048

## Accessories

050017

050108

## Related items

Pobrano z mamadecor.pl

89048T

89050L

89050TLD

## Physical Specification

| | |
|---|---|
| Item Group | 06 Downlights Fixed LED |
| Family | The 48W Square Panels Aluminium |
| Order Code | 50148E/W/W |
| Colour | White |
| Material | Aluminium |
| Diffuser Material | Acrylic |
| Shape | Rectangular |
| Length | 595mm |
| Width | 595mm |
| Height | 20mm |
| Recessed T-Ceiling | Yes |
| Depth Required | 50mm |
| Indoor | Yes |
| Adjustable | No |

## Electrical Characteristics

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 1200mA |
| Safety Class | |
| Power(Watts) | 48W |
| IP Rating | IP20 |
| Light Source | LED built in |

Pobrano z mamadecor.pl

| | |
|---|---|
| LED Type | SMD 2835 |
| LED Brand | Epistar |
| LED Number | 240 |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 4000lm |
| Light Efficiency | 83,33lm/W |
| CRI | 80 |
| Beam Angle | 120° |
| Illumination Diagram | |

## Packing Info

| | |
|---|---|
| Box Length | 72cm |
| Box Width | 65cm |
| Box Height | 4,5cm |
| Box Weight | 2,7Kg |
| Pcs/Carton | 6 |
| Barcode | 5291889041931 |
| HS Code | 9405109890 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 2 Years |

| | |
|---|---|
| Average Lifetime | 30000 hours |
| Weee Directive | Yes |

Pobrano z mamadecor.pl