Pobrano z mamadecor.pl

50148F/W/C

60x60 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with dimmable driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Related items

89050L

89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The 48W Square Panels Aluminium

Pobrano z mamadecor.pl

Order Code	50148F/W/C
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	595mm
Width	595mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	

Fitting

Input Type	Constant Current
Input Current	1200mA

Pobrano z mamadecor.pl

Safety Class	
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,4-50,4W
Power Factor	0.9
Constant Current	Yes
1200mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	Yes
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	3800lm
Light Efficiency	79,167lm/W
CRI	70
Beam Angle	120°
Illumination Diagram	

Packing Info

Pobrano z mamadecor.pl

Pcs/Carton	2
Barcode	5291889034889
HS Code	9405109890

Energy Label

Certification & Warranty

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes