Pobrano z mamadecor.pl

50148RE/W/D

120x30 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Must be ordered separately

89048

Accessories

050017

050108

Related items

Pobrano z mamadecor.pl

89048T

89050L

89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Rectangular Panels Aluminium
Order Code	50148RE/W/D
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	1195mm
Width	295mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	1200mA
Voltage	38V
Safety Class	
Power(Watts)	48W
IP Rating	IP20

Pobrano z mamadecor.pl

Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	240

Illumination Data

Colour Temperature	6000K
Lumen Output	4100lm
Light Efficiency	85,41lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Pcs/Carton	4
Barcode	5291889041986
HS Code	9405109890

Certification & Warranty

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes