Pobrano z mamadecor.pl

13 Wall & Ceiling LED>COB Outdoor Ceiling Cylinders

67516A/W/W

15W COB LED cylinder, IP65, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Physical Specification

Item Group	13 Wall & Ceiling LED
Family	COB Outdoor Ceiling Cylinders
Order Code	67516A/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	127mm
Diameter	83mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Pobrano z mamadecor.pl

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	36V
Power(Watts)	12,6W
IP Rating	IP65
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10,8-16W
Power Factor	0,9

Pobrano z mamadecor.pl

Constant Current	Yes
400mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KEGU

Illumination Data

Colour Temperature	3000K
Lumen Output	1200lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	40°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	9cm
Box Width	9cm
Box Height	16cm
Box Weight	0.725kg
Pcs/Carton	24
Barcode	5291889070108
HS Code	9405413990

Pobrano z mamadecor.pl

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes