Pobrano z mamadecor.pl

19 Wall Recessed & Inground>The COB Inground Range 2-6W

69028/W

2W COB LED inground, IP67, stainless steel 316, for path illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

Downloads

Dimensions

Gallery

Physical Specification

Item Group	19 Wall Recessed & Inground
Family	The COB Inground Range 2-6W
Order Code	69028/W
Colour	Stainless Steel
Material	Stainless Steel 316
Diffuser Material	Glass
Shape	Circular

Pobrano z mamadecor.pl

Height	100mm
Diameter	55mm
Cutout Hole Diameter	86mm
Inground	Yes
Depth Required	100mm+300mm drainage
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2W
IP Rating	IP67
Light Source	LED built in
Dimmable	No
Cable Length	50cm
F Mark	

Fitting

Input Type	Constant Current
Input Current	600mA
Voltage	3V
Safety Class	
Power(Watts)	1,8W
IP Rating	IP67

Pobrano z mamadecor.pl

Light Source	LED built in
LED Type	COB
LED Brand	Osram

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2W
Power Factor	0,9
Constant Current	Yes
600mA	3V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~+55°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	BTEC
Protection	Short Circuit

Illumination Data

Colour Temperature	3000K
Lumen Output	65lm
Light Efficiency	32,5lm/W
CRI	80
Beam Angle	30°
Illumination Diagram	

Pobrano z mamadecor.pl

Packing Info

Box Weight	0,5Kg
Barcode	5291889038702
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Average Lifetime	50000Hours
Weee Directive	Yes