Pobrano z mamadecor.pl

SHIELDECO 800 TILT

The SHIELDECO is a revolutionary Fire Rated dimmable LED downlight in both performance and installation. Utilising the tool-less fast fix 4 way loop in loop out connection system, the whole product can be fully wired and installed in a matter of seconds. Available in 4w 500 lumen and 8.5w 820 lumen and in both fixed and tilt versions. Owing to its unique construction and heat dissipation the product can be covered directly with insulation when installed in the ceiling. Suitable for both domestic and commercial applications this IP65 range of downlights are available in white, satin nickel and polished chrome.

NEW PRODUCT

FIRE RATED

DIMMABLE

FAST FIX

Can be covered with insulation

- Constructed from steel & acrylic
- 8.5W LED module (SMD)
- Angle of tilt: 20°
- Compatible dimmer 75021 (150W), see page 282

CODE	DESCRIPTION	FINISH	K	LM	LM/W	DIMENSIONS	CUT OUT
78520	ShieldECO 800 Tilt 8.5W	Matt white	3000	750	88	Proj: 3-15mm D: 60mm Dia: 85mm	Dia 70mm
78521	ShieldECO 800 Tilt 8.5W	Matt white	4000	820	96	Proj: 3-15mm D: 60mm Dia: 85mm	Dia 70mm
78522	ShieldECO 800 Tilt 8.5W	Satin nickel	3000	750	88	Proj: 3-15mm D: 60mm Dia: 85mm	Dia 70mm
78523	ShieldECO 800 Tilt 8.5W	Satin nickel	4000	820	96	Proj: 3-15mm D: 60mm Dia: 85mm	Dia 70mm
78524	ShieldECO 800 Tilt 8.5W	Chrome plate	3000	750	88	Proj: 3-15mm D: 60mm Dia: 85mm	Dia 70mm
78525	ShieldECO 800 Tilt 8.5W	Chrome plate	4000	820	96	Proj: 3-15mm D: 60mm Dia: 85mm	Dia 70mm

SHIELDECO 500 CCT

The SHIELDECO CCT is a CCT Fire Rated dimmable LED downlight. Utilising the tool-less fast fix 4 way loop in loop out connection system, the whole product can be fully wired and installed in a matter of seconds. This CCT downlight has two colour temperatures, warm white and cool white, in one fitting. Just flick the switch on the back of the product to choose either 3000K or 4000K. Available in a 4w 500 lumen output this versatile IP65 downlight comes complete with three interchangeable bezels white, satin nickel and polished chrome. Owing to its unique construction and heat dissipation the product can be covered directly with insulation when installed in the ceiling.

SHIELD ECO

NEW PRODUCT

FIRE RATED

CCT 3000/4000K

DIMMABLE

FAST FIX

3000K

4000K

Can be covered with insulation

CCT switch

Interchangable bezels supplied

- Constructed from steel & acrylic
- 4W LED module (SMD) CCT
- Min void: 90mm
- Compatible dimmer 75021 (150W), see page 282

CODE	DESCRIPTION	K	LM	LM/W	DIMENSIONS	CUT OUT
78519	ShieldECO 500 CCT 4W	3000/4000	500	125	Proj: 3mm D: 64mm Dia: 81.5mm	Dia 57mm